

Safety Data Sheet **Fabric Paint**

10 16 May 2020

SECTION 1	Product & Supplier Identification
Product Name	Fabric Paint Fabric & Craft Paint
Product Code	EC1205, EC1206, EC1207, EC1211, EC1208, EC1212, EC1209
	EC1210
Recommended Use	Paint for use on fabric (natural fibres, cotton). Hot iron to make fast.
Restrictions on Use	None known
Company	Modern Teaching Aids Pty Ltd
ABN	98 000 628 786
Address	Level 1, 122-126 Old Pittwater Road, Brookvale, NSW, Australia 2086
Telephone	1800 251 497
Supplier Code Emergency	
Phone Number	Australia – 13 11 26 (Poisons Information Centre)
SECTION 2	Hazards Identification
Classification of the bazardous	chemical
Classification of the hazardous of the hazardous of the hazards	chemical Not classified
Classification of the hazardous of Physical hazards Health hazards	
Physical hazards	Not classified
Physical hazards Health hazards Environmental hazards	Not classified Not classified Not classified
Physical hazards Health hazards Environmental hazards Label elements, including preca	Not classified Not classified Not classified
Physical hazards Health hazards Environmental hazards	Not classified Not classified Not classified utionary statements

Precautionary statementsPreventionResponseStorageStore in well ventilated place. Keep container tightly closed.

Disposal Dispose of contents and container in accordance with local regulations.

	ingreatent composition / internat	
Chemical Entity	CAS No.	Proportion (to 100%)
2-methylisothiazol-3(2H)-one	2682-20-4	< 0.01 %
Pyrithione zinc	13463-41-7	< 0.01 %
1,2-Benzisothiazolin-3(2H)-one	2634-33-5	< 0.01 %
Methanol	67-56-1	<0.005%
Formaldehyde	50-00-0	<0.001%
Non-hazardous components		to 100 %
SECTION 4	First Aid Measures	

Ingredient Composition / Information

Description of necessary first aid measures

SECTION 3

Eye Irrigate with copious quantities of water for atleast 15 minutes, lifting eyelids occasionally. Seek medical attention.
 Skin Wash off with soap and water. If any symptoms arise seek medical attention.
 Inhalation Move to a well ventilated area. Seek medical attention if symptoms persist.
 Swallowed Rinse mouth with water. Give water to drink. Seek medical attention if symptoms persist.

Personal protection for first aid responders

Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Symptoms caused by exposure

Direct contact with eyes may cause minor irritation. Direct contact with skin may cause minor irritation.

Medical attention and special treatment

Provide general supportive measures and treat symptomatically. Keep under observation as symptoms may be delayed. Seek medical attention if symptoms persist.

SECTION 5	Fire Fighting Measures	

Extinguishing equipment

Suitable Water, fog, foam, dry chemical powder, carbon dioxide. When choosing extinguishing equipment be aware of any potential hazard(s), example electrical.

Unsuitable Anything that could spread the fire and or risk the safety of surrounding personnel.

Specific hazards arising from the chemical

This product is water based and does not burn. It may however support combustion when the water has been removed and gases hazardous to health maybe formed.

Specific protective equipment and precautions for fire fighters

Self-contained breathing apparatus (SCBA) and full protective clothing (PPE) must be worn in case of fire.

Hazchem Code Not available.

General fire hazards No unusual fire or explosion hazards known.

SECTION 6

Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary people away of spill / leak. Wear protective equipment during clean up. Contain spill to prevent entry to drains / water ways. Local authorities should be contacted if spill cannot be contained. Collect and seal in clearly labelled containers for disposal in accordance with local regulations. Heed advice under Section 8 "Personal Protection".

For emergency responders

Keep unnecessary people away. Heed advice under Section 8 "Personal Protection".

Environmental precautions

Avoid discharge to drains, water ways or onto the ground.

Methods and materials for containment and clean up

Large spills – If safe to do, so stop flow of material and contain spill. Absorb spill in sand, vermiculite, dry earth or other inert absorbent material. Collect and seal in clearly labelled containers for disposal in accordance with local regulations.

Small spills – Wipe / clean up with absorbent material, e.g. cloth.

SECTION 7

Handling & Storage

Precautions for safe handling

Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in a cool, sheltered location away from direct sunlight and sources of heat. Keep containers tightly closed when not in use. Store in clearly labelled containers.

SECTION 8	Expos	sure Controls / Personal Prote	ection
Occupational ex	posure limits (OEL's No OEL's noted f Formaldehyde Methanol) or this specific product. Howeve 50-00-0 1.2 mg/m³(TWA) 67-56-1 262 mg/m³(TWA)	2.5 mg/m ³ (STEL)
Biological limit v		osure values noted for this prod	uct.
Appropriate eng	ineering controls Use in a well ven station.	tilated area. If required use loca	l exhaust ventilation. Provide an eyewash
Individual protec Eye prote	•	xample personal protective e	quipment (PPE)
	Wear safety gogg	les.	
Skin prote	, , , ,		
•	Wear impervious	gloves.	
	•• Llos and maintain	and inductive burgings. Always	week kende ofter wee. Deutinely

Hygiene measures Use and maintain good industrial hygiene. Always wash hands after use. Routinely maintain safety equipment. Do not eat, smoke or drink when handling this product.

SECTION 9 Physical & Chemical Properties
--

Coloured, thixotropic liquid. Slight odour Not available between 7.0 – 8.5 Not available Not available Not available Not flammable (In liquid form) Not available Not available Not available Dispersible between 1.01 – 1.12
between 1.01 – 1.12

SECTION 10

Stability & Reactivity

Reactivity This product is considered non-reactive under normal conditions of use, storage and transport.

Chemical stability This product is considered stable under normal conditions of use, storage and transport.

Possibility of hazardous reactions

No hazardous reaction known under normal use.

Conditions to avoid No specific data available for this product.

Incompatible materials

Strong oxidising agents and acids.

Hazardous decomposition

If engulfed in fire product may give rise to the release of obnoxious fumes including oxides of carbon.

SECTION 11	Toxicological Information
Information on noo	sible reutes of expective
Inhalation	sible routes of exposure No adverse effects expected due to inhalation.
	Minor irritation may be expected in some individuals.
	Minor irritation may be expected in some individuals.
Ingestion	Expected to be low ingestion hazard.
-	
Symptoms related t	
	Minor irritation in some individuals, Skin contact - symptoms may include redness, heat and itching.
	Eye contact - symptoms may include redness, near and iteming.
	Lye contact - symptoms may morate stinging and realless.
Acute	No specific data available.
Skin corrosion / irri	tation
	Prolonged skin contact may cause minor irritation in some individuals.
Serious eye damage	e / irritation
	May cause minor irritation in some individuals.
Deenington, on okin	
Respiratory or skin	Not a respiratory sensitizer.
	Not expected to cause skin sensitisation.
	Not expected to cause skill sensitisation.
Carcinogenicity	No data available.
Reproductive toxici	ty
•	This product is not expected to cause reproductive or developmental effects.
Additional Informat	ion
	does NOT contain,
	Egg, dairy, soy, seafood, shellfish, wheat or peanut products, by-products or derivatives.
SECTION 12	Ecological Information
Ecotoxicity	No specific data is available for this product. However, do not release this product or any
	water contaminated with this product into drains, soils or waterways. Sufficient measures
	should be taken to retain the water used in extinguishing any fires involving this product.
	Dispose of contaminant in accordance with local landfill or incineration regulations.
Persistence and de	gradability
	No specific data available.
Bio accumulative p	otential
bio accumulative p	No specific data available.
Mobility in soil	No specific data available.
SECTION 13	Disposal Considerations
Disposal methods	Dispose of this product and any water contaminated with this product in accordance with
	local regulations.
Contaminated pack	aging
	The container in which the product is/was contained should also be disposed of in

The container in which the product is/was contained should also be disposed of in accordance with local regulations.

SECTION 14	Transport Information
ADG	Not regulated as dangerous goods.
ΙΑΤΑ	Not regulated as dangerous goods for IATA
IMDG	Not regulated as dangerous goods.
Special Precautions	s No special precautions or requirements for transport
SECTION 15	Regulatory Information
Safety, health and e	environmental regulations
	This Safety Data Sheet was prepared in accordance with Safe Work Australia's Code of
	Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals.
_	
Standard for the Un	iform Scheduling of Medicines and Poisons (SUSMP)
	Not allocated
AICS	All components are listed in the Australian Inventory of Chemical Substances.
AICO	Air components are listed in the Australian inventory of Chemical Substances.
SECTION 16	Other Information
SECTION 16	Other Information
SECTION 16 Reason for Revision	
Reason for Revision	n Review and update information in accordance with GHS requirements.
Reason for Revision Update	n Review and update information in accordance with GHS requirements. Section 3 and Section 9 information changes.
Reason for Revision	 Review and update information in accordance with GHS requirements. Section 3 and Section 9 information changes. The TWA (Time Weighted Average) exposure value is the average airborne concentration
Reason for Revision Update	 Review and update information in accordance with GHS requirements. Section 3 and Section 9 information changes. The TWA (Time Weighted Average) exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day
Reason for Revision Update	 Review and update information in accordance with GHS requirements. Section 3 and Section 9 information changes. The TWA (Time Weighted Average) exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The term "peak" is used when the TWA limit, because of the rapid action of
Reason for Revision Update TWA	 Review and update information in accordance with GHS requirements. Section 3 and Section 9 information changes. The TWA (Time Weighted Average) exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded even briefly.
Reason for Revision Update	 Review and update information in accordance with GHS requirements. Section 3 and Section 9 information changes. The TWA (Time Weighted Average) exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded even briefly. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but
Reason for Revision Update TWA	 Review and update information in accordance with GHS requirements. Section 3 and Section 9 information changes. The TWA (Time Weighted Average) exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded even briefly. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more
Reason for Revision Update TWA	 Review and update information in accordance with GHS requirements. Section 3 and Section 9 information changes. The TWA (Time Weighted Average) exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded even briefly. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but
Reason for Revision Update TWA	 Review and update information in accordance with GHS requirements. Section 3 and Section 9 information changes. The TWA (Time Weighted Average) exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded even briefly. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures
Reason for Revision Update TWA STEL	 Review and update information in accordance with GHS requirements. Section 3 and Section 9 information changes. The TWA (Time Weighted Average) exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded even briefly. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. Safe Work Australia
Reason for Revision Update TWA STEL SWA	 Review and update information in accordance with GHS requirements. Section 3 and Section 9 information changes. The TWA (Time Weighted Average) exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded even briefly. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL.
Reason for Revision Update TWA STEL SWA ADG	 Review and update information in accordance with GHS requirements. Section 3 and Section 9 information changes. The TWA (Time Weighted Average) exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded even briefly. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. Safe Work Australia Australian Dangerous Goods Code
Reason for Revision Update TWA STEL SWA ADG AICS	 Review and update information in accordance with GHS requirements. Section 3 and Section 9 information changes. The TWA (Time Weighted Average) exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded even briefly. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. Safe Work Australia Australian Dangerous Goods Code Australia Inventory of Chemical Substances

Whilst every care has been taken in compiling these instructions, Modern Teaching Aids Pty Ltd, its employees, contractors and agents neither warrant nor represent that the material published herein is accurate or free from errors or omissions. To the extent permissible by law, Modern Teaching Aids Pty Ltd, its employees, contractors and agents shall not be liable or responsible for any errors, omissions or misrepresentations made herein.

Date Printed : 5 January 2022